

**Issued in : March 2004****Serial No: 1/04****MOISTURE LEVELS OF BLACK TEA***(This replaces the Advisory Circular No. T7, Serial No. 2/81)*

The most important factor that determines the keeping qualities of tea is the moisture content. At high moisture levels the deterioration of the desirable tea characteristics is faster and these teas are found to lose briskness with time and end up as flat teas. The moisture content of tea could be kept within the desired limits by the following:

- i) Proper drying of tea.
- ii) Preventing excessive moisture absorption during grading and,
- iii) Packing tea in proper containers such as plywood tea chests lined with aluminium foil or multiwall paper sacks.

The moisture content of properly fired dhools when sampled at the drier mouth should be in the region of 3% and that of the tea at the time of packing should preferably be less than 5%.

In order to dry tea properly, the following operating conditions are recommended for the ECP Drier and the Fluid Bed Drier (FBD):

ECP

- a) Inlet air temperature of 190 -195 °F (88 - 91°C).
- b) Exhaust air temperature - recorded by a thermometer placed one-third the length away from feed end and 6 inches (15.2 cm) above top tray of 125-135 °F (52 – 57°C).
- c) Residence time (i.e. time through the drier) of 21 minutes.
- d) Air volume of 30 cfm per lb (1.87 cubic meters per minute per kg) moisture evaporated per hour, with uniform distribution over the top tray.
- e) By-pass valve at fully closed position.
- f) Adjustment of feed rate so as to maintain recommended exhaust temperature.
- g) The fall through of tea should be minimized by having suitable tray perforations.

FBD

- a) Inlet air temperature of 260 °F (127°C).
- b) Height of discharge weir in drier at 3 ½ - 4 inches (8.9 – 10 cm).
- c) Tea bed temperature near discharge end (recorded by a thermo probe immersed in the tea bed and mounted 6 to 8 inches (15.2 – 20.3 cm) from the discharge weir of the drying chamber) at 190-200 °F (88 – 93°C).
- d) Air volume of 2000-2500 cfm (56.6 – 71 cubic meters per minute) per drying section.
- e) Volume control dampers adjusted so as to get well fluidized tea bed in all sections and,
- f) Adjustment of feed rate so as to maintain the recommended tea bed temperature near discharge end.